

# SUREFLOOR UHS .A. COLOUR

Infosafe™  
No.

Issue Date July 2006

Status ISSUED by

BS: 1.9.12

## Resins

---

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

---

Product Name SUREFLOOR UHS.A.COLOUR

Product Code

Company Name Con-Treat Pty Ltd

Address Australia: Unit 11, 80-82 Township Drv Burleigh QLD 4220

Emergency Tel. 1800 022 037 (24H)

Telephone/Fax Tel:  
Number Fax:

Recommended Use Flooring compound.

Other Names Not Available

Other  
Information

---

### 2. HAZARDS IDENTIFICATION

---

#### Hazard Classification

---

Australia:

Classified as Hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC), Australia.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

New Zealand:

Classified as Hazardous according to the New Zealand Hazardous Regulations 2001.

Classified as Dangerous Goods for transport, according to the New Zealand Standard NZS 5433:1999 Transport of Dangerous Goods on Land.

**Risk Phrase(s)**

R43 May cause sensitization by skin contact.  
 R36/38 Irritating to eyes and skin.  
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety Phrase (s)**

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
 S28 After contact with skin, wash immediately with plenty of soap and water.  
 S61 Avoid release to the environment. Refer to special instructions/safety data sheet.  
 S24/25 Avoid contact with skin and eyes.  
 S37/39 Wear suitable gloves and eye/face protection.

---

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

| Ingredients | Name  | CAS        | Proportion      |
|-------------|---|------------|-----------------|
|             | Epoxy Resin (number average molecular weight <= 700)                        | 25068-38-6 | 60-70 %         |
|             | Butanedioldiglycidyl ether  | 2425-79-8  | 0-10 %          |
|             | Ingredients determined not to be hazardous                                  |            | Balance to 100% |
|             | Bisphenol F-epichlorohydrin resin with Number Average Molecular Weight <700 | 28064-14-4 | 10-30 %         |

---

### 4. FIRST AID MEASURES

---

|                   |  |
|-------------------|--|
| <b>Inhalation</b> | Remove the source of contamination or move the victim to fresh air. Ensure airways are clear and have qualified person give oxygen through a face mask if breathing is difficult. Apply artificial respiration if not breathing. Seek medical attention. |
| <b>Ingestion</b>  | Do not induce vomiting. Wash out mouth with copious amounts of water. Seek medical attention.  |
| <b>Skin</b>       | If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Wash contaminated clothing before re-use. If irritation occurs seek medical advice.   |
| <b>Eye</b>        | If contact with the eye(s) occur, wash with running water holding eyelid(s) open. Take care not to rinse contaminated water into the non-affected eye. In all cases of eye contamination it is a sensible precaution to seek medical advice.             |

**First Aid**

|                          |  |
|--------------------------|--|
| <b>Facilities</b>        | Eye wash and normal washroom facilities.   |
| <b>Advice to Doctor</b>  | Treat symptomatically.   |
| <b>Other Information</b> | For advice, contact a Poisons Information Centre (Phone eg Australia 131 126) or a doctor at once. |

## 5. FIRE FIGHTING MEASURES

|  |  |
|--|--|
| <b>Suitable Extinguishing Media</b>        | Use carbon dioxide, dry chemical, and foam or water mist.  |
| <b>Hazards from Combustion Products</b>    | Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.              |
| <b>Hazchem Code</b>                        | 2X   |
| <b>Precautions in connection with Fire</b> | Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode. |
| <b>Unsuitable Extinguishing Media</b>      | Water in a jet.  |

## 6. ACCIDENTAL RELEASE MEASURES

|                             |  |
|-----------------------------|--|
| <b>Emergency Procedures</b> | Wear appropriate personal protective equipment and clothing to minimise exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unnecessary personnel. If possible contain the spill. Place inert absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. Do not dilute material but contain. Dispose of waste according to federal, Environmental Protection Authority and state regulations. If the spillage enters the waterways contact the Environmental Protection Authority, or your local Waste Management Authority. |
|-----------------------------|--|

## 7. HANDLING AND STORAGE

|                                      |  |
|--------------------------------------|--|
| <b>Precautions for Safe Handling</b> | Use in a well ventilated area. DO NOT store or use in confined spaces. Build up of mists or vapours in the atmosphere must be prevented. Avoid breathing in spray or mists or vapours. Do not use near welding or other ignition sources and avoid sparks. Do not smoke. When dealing with this product, repeated or prolonged skin exposure without protection should be prevented in order to lessen the possibility of skin disorders. It is essential that all who come into contact with this material maintain high standards of personal hygiene ie. Washing hands prior to eating, drinking, smoking or using toilet facilities. |
|--------------------------------------|--|

**Conditions for Safe Storage** Classified as a Class C2 (COMBUSTIBLE LIQUID) for the purposes of storage and handling. Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**National Exposure Standards** No exposure standards have been established for this material by the Australian National Occupational Health & Safety Commission (NOHSC) or the Occupational Safety and Health Service (OSH) of the New Zealand Department of Labour. However, over-exposure to any chemical may result in enhancement of pre-existing adverse medical conditions and/or allergic reactions and should be kept to the least possible levels.

**Biological Limit Values** No biological limit allocated.

**Engineering Controls** Good ventilation adequate to maintain the airborne contamination below target levels or exposure standards is required. The use of a local exhaust ventilation system (drawing vapours/mists away from workers breathing zone) is recommended. If the engineering controls are not sufficient to maintain concentrations of particulates and vapours below the exposure standards, suitable respiratory protection must be worn.

**Respiratory Protection** If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.

**Eye Protection** Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

**Hand Protection** Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

**Body Protection** Suitable work wear should be worn to protect personal clothing,

eg cotton overalls buttoned at neck and wrist. When large quantities are handled the use of plastic aprons and rubber boots is recommended. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

**Appearance** Coloured thick liquid.

**Odour** Not available.

**Melting Point** Not available.

**Boiling Point** Not available.

**Solubility in Water** Insoluble.

**Specific Gravity** 1.506

**pH Value** Not available.

**Vapour Pressure** Not available.

**Vapour Density (Air=1)** Not available.

**Viscosity** 2600 cP

**Flash Point** >150°C

**Auto-Ignition Temperature** Not available.

**Flammable Limits - Lower** Not available.

**Flammable Limits - Upper** Not available.

---

## 10. STABILITY AND REACTIVITY

---

**Chemical Stability** Stable under normal conditions.

**Conditions to Avoid** Heat, direct sunlight, open flames or other sources of ignition.

**Incompatible Materials** Bisphenol A and F:  
 Reacts with strong oxidising agents. Polymerises exothermically with amines, mercaptans and Lewis acids at ambient temperature and above. Polymerises in contact with caustic soda. Reacts exothermically with bases (eg caustic soda), ammonia, primary and secondary amines, alcohols and acids.

**Hazardous**

**Decomposition Products** Thermal decomposition may result in the release of toxic and/or irritating fumes.

**Hazardous Polymerization** Bisphenol A and F:  
Polymerises exothermically with amines, mercaptans and Lewis acids at ambient temperature and above. Polymerises in contact with caustic soda.

---

## 11. TOXICOLOGICAL INFORMATION

---

**Inhalation** Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

**Ingestion** Ingestion of this product may cause irritation to the gastric tract and upper respiratory tract, causing nausea, diarrhoea and vomiting.

**Skin** Will cause irritation in contact with skin, resulting in redness, itching and dermatitis. May cause sensitisation by skin contact.

**Eye** Irritating to eyes. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

**Chronic Effects** Prolonged or repeated skin contact may lead to allergic contact dermatitis and sensitisation in some individuals.

---

## 12. ECOLOGICAL INFORMATION

---

**Ecotoxicity** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Persistence / Degradability** No data is available for this material.

**Mobility** No data is available for this material.

**Environment Protection** Do not allow product to enter drains, waterways or sewers.

---

## 13. DISPOSAL CONSIDERATIONS

---

**Disposal Considerations** Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

---

## 14. TRANSPORT INFORMATION

---

**Transport** Australia:

**Information** This material is classified as a Class 9 (Miscellaneous Dangerous Goods) Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. Dangerous goods of Class 9 (Miscellaneous Dangerous Goods) are incompatible in a placard load with any of the following:

- Class 1, Explosive
- Class 5.1, if the Class 9 substance is a fire risk substance
- Class 5.2, if the Class 9 substance is a fire risk substance

New Zealand:

This material is classified as a Class 9 - Miscellaneous Substance according to NZS 5433:1999 Transport of Dangerous Goods on Land.

Must not be loaded in the same freight container or on the same vehicle with:

- Class 1, Explosives

Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices with:

(Note 3; Segregation devices may be used as to segregate dangerous goods of Class 9 when the nature of those dangerous goods requires them to be segregated from dangerous goods of);

- Class 3, Flammable liquids
- Class 4.1, Flammable solids
- Class 4.2, Spontaneously combustible substances
- Class 4.3, Dangerous when wet substances
- Class 5.1, Oxidising substances
- Class 5.2, Organic peroxides
- Class 6.1, Toxic substances
- Class 6.2, Infectious substances
- Class 8, Corrosive substances

And are incompatible with food and food packaging in any quantity.

|                             |   |
|-----------------------------|---|
| <b>U.N. Number</b>          | 3082  |
| <b>Proper Shipping Name</b> | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. - (CONTAINS BISPHENOL A AND BISPHENOL F EPOXY RESINS) |
| <b>DG Class</b>             | 9   |
| <b>Hazchem Code</b>         | 2X  |
| <b>Packaging Method</b>     | 3.8.9   |
| <b>Packing Group</b>        | III   |
| <b>EPG Number</b>           | 9C1   |
| <b>IERG Number</b>          | 47  |

---

## 15. REGULATORY INFORMATION

---

**Regulatory Information** Australia:  
Classified as hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC).  
Poison Schedule: Schedule 5

New Zealand:  
Classified as Hazardous according to the Hazardous Substances

(Classification) Regulations 2001.  
Not scheduled according to the Toxic Substances Regulations  
1983.

**Poisons  
Schedule** S5

S5 New Zealand:Not Scheduled

**Hazard Category** Irritant,Dangerous for the environment

---

## 16. OTHER INFORMATION

---

**Date of  
preparation or  
last revision  
of MSDS**

MSDS created: July 2006.

**Contact  
Person/Point**

Australia: Business Hours:  
Telephone:  
Emergency Tel: 1800 022 037

New Zealand: Business Hours:  
Emergency Tel:

IMPORTANT ADVICE: This MSDS summarizes our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including its use in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Con-Treat Pty Ltd. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

---

End of MSDS

---



# Material Safety Data Sheet

## SUREFLOOR UHS PART B SLOW

**Infosafe No.** 1HLAQ **Version No.** **ISSUED** May **Status** ISSUED  
**Date** 2009

**Classified as hazardous according to criteria of NOHSC**

---

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

---

**Product Name**

SUREFLOOR UHS PART B SLOW

**Product Code****Company Name**

Con-Treat PTY LTD

**Address**

Australia:

Unit 11, 80-82 Township Drive Burleigh Heads, QLD 4220

**Emergency Tel.**

Australia: 1800 022 037

**Telephone/Fax Number**

Telephone: Australia:

**Email**

info@con-treat.com.au

**Recommended Use**

Curing agent for epoxy resins - flooring.

---

### 2. HAZARDS IDENTIFICATION

---

**Hazard Classification**

Australia:

Classified as Hazardous, according to criteria of National Occupational Health & Safety Commission, Australia (NOHSC).

Classified as Dangerous Goods, according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

New Zealand:

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

Classified as Dangerous Goods for transport, according to the NZS 5433:2007 Transport of Dangerous Goods on Land.

HSNO Classification:

6.1D - Substance that is acutely toxic if swallowed and in contact with skin.

6.5B - Substance that is a contact sensitiser.

- 6.8B - Substance that is a suspected human reproductive or developmental toxicant.
- 8.2C - Substance that is corrosive to dermal tissue.
- 8.3A - Substance that is corrosive to ocular tissue.
- 9.1C - Substance that is ecotoxic in the aquatic environment.
- 9.2B - Substance that is ecotoxic in the soil environment.
- 9.3C - Substance that is toxic to terrestrial vertebrates.

Hazard statement code:

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H332 Harmful if inhaled.
- H317 May cause an allergic skin reaction.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H361 Suspected of damaging fertility or the unborn child.
- H412 Harmful to aquatic life with long lasting effects.
- H422 Toxic to the soil environment.
- H433 Harmful to terrestrial vertebrates.

Precautionary statement codes- prevention:

- P102 Keep out of reach of children. - This statement applies only where the substance is available to the general public.
- P103 Read label before use. - This statement applies only where the substance is available to the general public.
- P104 Read Safety Data Sheet before use.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe mist/vapours/spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment. - This statement does not apply where this is the intended use.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement codes- Response:

- P101 If medical advice is needed, have product container or label at hand. - This statement applies only where the substance is available to the general public.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P391 Collect spillage.
- INHALATION:
  - P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
  - P312 Call a POISON CENTRE or doctor/physician if you feel unwell.
  - P331 Do NOT induce vomiting.
- INGESTION:
  - P301+P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
  - P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- SKIN:
  - P302+P352 IF ON SKIN: Wash with plenty of soap and water.
  - P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
  - P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
  - P363 Wash contaminated clothing before reuse.
  - P310 Immediately call a POISON CENTRE or doctor/physician.
- EYES:
  - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
  - P310 Immediately call a POISON CENTRE or doctor/physician.

Precautionary statement codes - Storage:

- P405 Store locked up.

Precautionary statement codes - Disposal:

- P501 \*In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided.

**Risk Phrase(s)**

R34 Causes burns.

R43 May cause sensitization by skin contact.

R62 Possible risk of impaired fertility.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

### Safety Phrase (s)

S23 Do not breathe gas/fumes/vapour/spray

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S45 In case of accident or if you feel unwell seek medical advice immediately

S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

S24/25 Avoid contact with skin and eyes.

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

---

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

### Ingredients

| Name                         | CAS        | EINECS    | Proportion |
|------------------------------|------------|-----------|------------|
| Isophorone diamine           | 2855-13-2  | 220-666-8 | 30-60 %    |
| Benzyl Alcohol               | 100-51-6   | 202-859-9 | 30-60 %    |
| 1,5-pentanediamine, 2-methyl | 15520-10-2 | 239-556-6 | 10-30 %    |
| BISPHENOL A                  | 80-05-7    | 201-245-8 | 0-<10 %    |

---

## 4. FIRST AID MEASURES

---

### Inhalation

If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. Seek IMMEDIATE medical attention.

### Ingestion

Do NOT induce vomiting. Wash out mouth with water. Seek IMMEDIATE medical attention.

### Skin

Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. Seek IMMEDIATE medical attention.

### Eye

If contact with the eye(s) occurs, wash with copious amounts of water holding eyelid(s) open. Take care not to rinse contaminated water into the non-affected eye. Seek IMMEDIATE medical attention.

### First Aid Facilities

Eye wash station, safety shower and normal washroom facilities.

### Advice to Doctor

Treat symptomatically.

### Other Information

For advice, contact a Poisons Information Centre (Phone eg Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

---

## 5. FIRE FIGHTING MEASURES

---

### Suitable Extinguishing Media

Water spray, carbon dioxide, foam or dry powder.

### Hazards from Combustion Products

Combustion may produce Carbon monoxide, carbon dioxide, oxides of nitrogen, ammonia,

amines, fumes and smoke.

### Specific Hazards

Combustible liquid. This product will burn if exposed to fire.

### Hazchem Code

2X

### Precautions in connection with Fire

Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode. Water spray may be used to keep fire exposed containers cool.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

### Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water authorities and EPA in accordance with local regulations.

---

## 7. HANDLING AND STORAGE

---

### Precautions for Safe Handling

Corrosive liquid. Attacks skin and eyes. May produce severe burns. Wear suitable protective clothing, gloves and eye/face protection when mixing and using. Use in designated areas with adequate ventilation. Avoid breathing in vapours, mist or fumes. Keep containers closed when not in use. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands after handling, and before eating, drinking, smoking or using the toilet facilities.

### Conditions for Safe Storage

Store in a cool dry well-ventilated area. Store away from oxidising agents and bases/acids. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Provide a catch-tank in a bunded area. Store in original packages as approved by manufacturer. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. For information on the design of the storeroom, reference should be made to Australian Standard AS 3780-1994 The storage and handling of corrosive substances. Reference should also be made to all State and Federal regulations.

### Storage Regulations

Classified as a (COMBUSTIBLE LIQUID) for the purposes of storage and handling, in accordance with the requirements of AS1940. This product should be stored and used in a well ventilated area away from naked flames, sparks and other sources of ignition.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### National Exposure Standards

No exposure standards have been established for this material by the Australian National Occupational Health & Safety Commission (NOHSC) or the Occupational Safety and Health Service (OSH) of the New Zealand Department of Labour. However, as with all chemicals, exposure should be kept to the lowest possible levels.

### Biological Limit Values

No biological limit allocated.

### Engineering Controls

Provide sufficient ventilation. Where vapours or mists are generated, a local exhaust ventilation system, drawing vapours/mists away from workers breathing zone, should be used.

### **Respiratory Protection**

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapour/mist filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

### **Eye Protection**

Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

### **Hand Protection**

Wear gloves of impervious material such as PVC or nitrile rubber gloves. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

### **Body Protection**

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### **Appearance**

Amber liquid.

### **Odour**

Amine odour.

### **Melting Point**

Not available

### **Boiling Point**

> 200°C

### **Solubility in Water**

Insoluble

### **Specific Gravity**

1.0

### **pH Value**

Not applicable.

### **Vapour Pressure**

Not available.

### **Vapour Density (Air=1)**

Not available.

### **Flash Point**

112°C

### **Flammability**

Combustible liquid.

**Auto-Ignition Temperature**

Not available.

**Flammable Limits - Lower**

Not available.

**Flammable Limits - Upper**

Not available.

---

## 10. STABILITY AND REACTIVITY

---

**Chemical Stability**

Stable under normal conditions of storage and handling.

**Conditions to Avoid**

Extremes of temperature and direct sunlight.

**Incompatible Materials**

Strong oxidising agents, acids, bases and epoxies.

**Hazardous Decomposition Products**

Carbon monoxide, carbon dioxide, oxides of nitrogen, ammonia, amines, fumes and smoke.

**Hazardous Reactions**

Will react with strong acids to produce heat.

**Hazardous Polymerization**

Will not occur.

---

## 11. TOXICOLOGICAL INFORMATION

---

**Toxicology Information**

Acute toxicity:

For Isophorone diamine:

LD50 Oral (rat): 1990 mg/kg.

For benzyl alcohol:

LD50 Oral (rat): 1230-1660 mg/kg

**Inhalation**

Harmful by inhalation. Inhalation of mists or vapours will result in respiratory irritation and possible harmful corrosive effects including lesions of the nasal septum, pulmonary edema, pneumonitis and emphysema.

**Ingestion**

Harmful if swallowed. Ingestion of this product may cause nausea, vomiting, abdominal pain and chemical burns to the mouth, throat and stomach.

**Skin**

Harmful in contact with skin. Corrosive to skin. Skin contact will cause redness, itching, irritation, severe pain and chemical burns with resultant tissue destruction. This product may cause sensitisation in some individuals.

**Eye**

Causes burns. Eye contact will cause stinging, blurring, tearing, severe pain and possible permanent corneal damage.

**Chronic Effects**

Allergic response and dermatitis or asthma like symptoms may occur after a single significant exposure, and sensitisation may occur on a single exposure, or multiple minor exposures.

**Reproductive Toxicity**

According to NOHSC this product is a category 3 Possible risk of impaired fertility.

---

## 12. ECOLOGICAL INFORMATION

---

**Ecotoxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Persistence / Degradability**

Not available

**Mobility**

Not available

**Environ. Protection**

Do not allow product to enter drains, waterways or sewers.

---

## 13. DISPOSAL CONSIDERATIONS

---

**Disposal Considerations**

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

---

## 14. TRANSPORT INFORMATION

---

**Transport Information****Australia:**

This material is classified as a Class 8 (Corrosive) Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. Dangerous goods of Class 8 (Corrosive) are incompatible in a placard load with any of the following:

- Class 1, Explosive
- Class 4.3, Dangerous When Wet Substance
- Class 5.1, Oxidising Agent
- Class 5.2, Organic Peroxide
- Class 6, Toxic and Infectious Substances, if the Class 6 dangerous goods are cyanides and the Class 8 dangerous goods are acids
- Class 7, Radioactive Substance

and are incompatible with food and food packaging in any quantity.

**New Zealand:**

This material is classified as a Class 8 - Corrosive Substance according to NZS 5433:2007 Transport of Dangerous Goods on Land.

Must not be loaded in the same freight container or on the same vehicle with:

- Class 1, Explosives
- Class 5.1, Oxidising substances
- Class 5.2, Organic peroxides
- Class 7, Radioactive materials unless specifically exempted

And are incompatible with food and food packaging in any quantity.

Note 1; Cyanides (Class 6.1) must not be loaded in the same freight container or on the same vehicle with acids (Class 8).

Note 2; Strong acids must not be loaded in the same freight container or on the same vehicle with strong alkalis. Packing Group I and II acids and alkalis should be considered as strong.

Must not be loaded with in the same freight container; and on the same vehicle must be separated horizontally by at least 3 metres unless all but one are packed in separate freight containers with:

- Class 4.3, Dangerous when wet substances

Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices with:

- Class 4.3, Dangerous when wet substances
  - Class 5.1, Oxidising substances
  - Class 5.2, Organic peroxides
- And are incompatible with food and food packaging in any quantity.

**U.N. Number**

1760

**Proper Shipping Name**

CORROSIVE LIQUID, N.O.S. - (CONTAINS ISOPHORONE DIAMINE)

**DG Class**

8

**Packing Group**

III

**Hazchem Code**

2X

**IERG Number**

37

---

## 15. REGULATORY INFORMATION

---

**Regulatory Information**

Australia:

Classified as hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC).

Classified as a Scheduled Poison S5 according to the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

**Poisons Schedule**

S5

**National and or International Regulatory Information**

New Zealand:

Classified as Hazardous according to the Hazardous Substances (Classification) Regulations 2001.

Group standard:

Additives, Process Chemicals and Raw Materials (Corrosive) Group Standard 2006  
HSNO Approval Number HSR002491.

**Hazard Category**

Harmful, Toxic for reproduction fertility Category 3, Dangerous for the environment, Sensitising

---

## 16. OTHER INFORMATION

---

**Date of preparation or last revision of MSDS**

MSDS Reviewed: May 2009

MSDS created: June 2004

**Contact Person/Point**

For specialist advice in emergencies: Australia 1800 022 037; New Zealand 0800 154 666.

IMPORTANT ADVICE: This MSDS summarizes our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including its use in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Con-Treat Pty Ltd. Our responsibility for products sold is subject to our standard terms and



conditions, a copy of which is sent to our customers and is also available on request.

---

End of MSDS

---

Con-Treat Pty Ltd