

TECHNICAL DATA SHEET

Concrete Shield Wet Look Premium

ISSUED: February 2015

INTRODUCTION

Concrete Shield™ Wet Look - Premium is a highly effective color enhancer and heavy duty sealing protection against most stains. It works quickly to enrich and darken the surface to provide a natural wet look finish.

USE

Concrete Shield™ Wet Look - Premium can be used for interior and exterior applications in warehouses, restaurants, retail shops and car parks.

FEATURES

Concrete Shield™ Wet Look - Premium

Enriches Color

Heavy duty protection against most stains

Can be used for interior and exterior applications

TECHNICAL DATA

Application Temperature	> -10°C & < 34°C
Colour	Transparent liquid – Dries Clear
Base	Solvent based
Coverage Rate	3–5 m ² /L porous surfaces, 20 m ² /L smooth, dense surfaces
Clean up	Wet: Mineral Spirits Dry: Mechanically
Pack Size	5L & 15L
Shelf Life	12 months unopened, store in cool, dry conditions.

APPLICATION

APPLICATION

SURFACE PREPARATION

Always test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results.

Make sure surface is clean, free of waxes, coatings, and previous sealers, and is dry for 24–72 hours.

Surface temperature should be between 10°C and 35°C. Ensure that the area is well-ventilated during application and until the surface is dry.

Mask off any surfaces not intended to be treated.

EQUIPMENT FOR APPLICATION

For small jobs, use a paint pad, roller, or brush.

For larger jobs, use a pump-up garden sprayer available at your local garden center or hardware store.

PLEASE NOTE: Do not use a power sprayer. Power sprayers create a significant amount of overspray, resulting in wasted product and the need for additional clean-up. A pump-up garden sprayer will reduce the potential for over-exposure to vapors and produce better results.

TECHNICAL DATA SHEET

APPLICATION CONTINUED

APPLICATION

Apply **Concrete Shield™ Wet Look – Premium** liberally and evenly using a paint pad, roller, brush, or pump-up garden sprayer.

PLEASE NOTE: Do not use a power sprayer, towel, or sponge for application. Do not thin before using.

Allow sealer to penetrate surface for 15–20 minutes. Denser material may require more time to penetrate. **DO NOT ALLOW EXCESS SEALER TO DRY ON SURFACE.** Failure to remove excess sealer from surface may result in residue that may need to be mechanically removed.

Thoroughly wipe surface with multiple dry cloths to remove all excess sealer. A second coat may be needed for more absorbent surfaces. If darker appearance is required, an additional coat of the sealer can be applied one hour after initial application.

Full cure is achieved after 24–72 hours. Avoid foot traffic for 6–8 hours after application.

CLEAN UP

Clean equipment with mineral spirits promptly after the job is complete.

PLEASE NOTE: Rags and equipment that are wet with product may be flammable.

Clean equipment with mineral spirits and allow to dry in a well-ventilated area.

SAFETY

Avoid contact with skin and eyes and avoid breathing the vapour or spray mist. Store under cover, out of direct sunlight and in a well ventilated area. Please refer to Fortis Safety Data Sheet . **Concrete Shield™ Wet Look – Premium** is safe if good working practices and proper application equipment is used. Good industrial hygiene should be observed at all times – Appropriate PPE should be worn including impervious gloves & eye wear.

First Aid

Eyes: If splashed in eyes, flush with water for 15min. Seek medical advice.

Skin: Wash affected area with soap and water.

Inhalation: If mists are inhaled, remove patient to fresh air. Seek medical advice.

Swallowed: Do NOT induce vomiting. Give milk or water to dilute. Seek medical advice.

For further information please refer to the Fortis Safety Data Sheet for this product.

Disclaimer

Fortis products should be used in accordance with the information contained here. Each user should read and consider this information carefully in the context of how the products will be handled and used in the workplace including in conjunction with other products. While the information contained here is to the best of our knowledge at the date of publication, Fortis makes no representation about the accuracy of the information. If you need clarification or more information, you should contact Fortis Adhesives & Coatings office directly. Fortis products are sold without express or implied warranties, other than as provided by statute, and subject to our standard terms and conditions (provided to customers and available on request). Subject to our standard terms and conditions, and any statutory provisions, Fortis accepts no responsibility (including in negligence) for loss or damage of any nature resulting from the use of Fortis Adhesives & Coatings products or reliance upon the information contained here
