

TECHNICAL DATA SHEET

Issue: 14-Oct-15

SEALER STRIPPER

This product is a very strong surface active agent formulated to soften existing damaged paint so that it can be removed.

FEATURES & BENEFITS

- * Softens old or damaged coatings
- * Does not contain methylene chloride

PERFORMANCE GUIDE & COMPARISON*

Product	Ease of Application	Preparation	Durability	Maintenance
Stripper Sealer	Medium	Low	N/A	N/A

Characteristic	Typical Value
Colour	Gel
Solids (vol. %)	<10%
Gloss	N/A
Pack Sizes	20 Litre
Abrasion Resistance	N/A
Chemical Resistance	N/A
Solvent Resistance	N/A

* Performance Guide & Comparison

Description	Evaluation and Meaning
Ease of Application	A low level of effort and expenditure to apply the coating, combined with level of expertise. <i>High = very easy to apply; Medium = easy to apply; Low = presents challenges for inexperienced users.</i>
Preparation	The level of effort and expense for preparing the substrate for coating. <i>High = a high level of effort and expertise required for preparation; Medium = modest preparation required; Low = low to no preparation required.</i>
Durability	The expected performance under standard Australian conditions for weathering and temperature variation. <i>High = High level of durability under extreme conditions; Medium = meets or exceeds standard conditions; Low = meets standard conditions, but not expected to endure.</i>
Maintenance	The level of continued coating support, or re-coating to achieve the same level of performance. <i>High = a high level of effort and expenditure in cleaning, or re-coating the system; Medium = a modest level of effort and expenditure for cleaning to keep the coating looking good and performing well; Low = almost no effort to support the coating system after application.</i>

TECHNICAL DATA SHEET

Issue: 14-Oct-15

APPLICATION

Apply using a solvent resistant broom.

Spread-rate:

	Minimum	Maximum	Typical
Theoretical Spread Rate (m ² /L)	1	3	2
Wet Film Thickness (µm)	N/A	N/A	N/A
Dry Film Thickness (µm)	N/A	N/A	N/A

Dry Times**

Substrate Temperature	5°C	10°C	20°C	30°C
Surface Dry (minutes)	N/A	N/A	N/A	N/A
Hard Dry (hours)	N/A	N/A	N/A	N/A
Recoat Time (hours)	N/A	N/A	N/A	N/A

** Drying times are generally related to air circulation, temperature, and film thickness. The figures given above are typical with good ventilation, typical film thickness and single coat application.

SURFACE PREPARATION

Remove any residue that will restrict the gel from penetrating the surface. Allow surface to fully dry as water will dilute and reduce gel activity.

DIRECTIONS FOR USE

Do not apply in direct sun. Start applying at the lowest point and pour stripper over 4 to 5 square metres then scrub into the surface using a solvent resistant broom. Allow stripper to soften the surface then scrape off and remove the majority of damaged paint. Remove remainder by water blasting away from area still to be stripped.

SAFETY

This product contains flammable solvents. Keep away from heat and flame. No smoking. Provide adequate ventilation and wear protective clothing. Consult the Safety Data Sheet.

Failure to observe these precautions will void all warranties and guarantees for product performance. The manufacturer will take no responsibility for coatings, products, labour, corrective action, or compensation where there is evidence of a failure to abide by the manufacturer's directions.

CLEAN UP

Wash up with water.

DISCLAIMER

Do not apply this product if there is uncertainty about application or surface preparation. This Product Data Sheet is to be used as a guide only; it is NOT a specification.